

- **Formed Steel Pressure Cap**
- **Corrosion Resistance e-Coating Standard**
- **Formed Steel Non-Pressure Chamber**
- **Heavy - Duty Nylon Reinforced Diaphragm**
- **Top and Side Air Ports - 3/8" NPTF**
- **Center Hole Shield**



CLASSIFY	DMS20D	DMS24D	DMS24E	DMS30D
----------	--------	--------	--------	--------

SIZE	20	24	24	30
STROKE	2.5" (63.5mm)	2.5" (63.5mm)	3" (76.2mm)	2.5" (63.5mm)
Wt. lb (kg)	6.92 lb (3.14kg)	8 lb (3.65kg)	8.8 lb (4kg)	10.1 lb (4.6kg)
1	4.39"/111.5mm	4.65"/118mm	5.12"/130mm	4.83"/122.7mm
2	3.66±0.12" 93±3mm	4.02±0.12" 102±3mm	4.50±0.12" 114.5±3mm	4.21±0.12" 107±3mm
3	1.54±0.05" 39±3mm	1.54±0.05" 39±3mm	1.54±0.05" 39±3mm	1.54±0.05" 39±3mm
4	1.45±0.12" 37±3mm	1.41±0.12" 37±3mm	1.45±0.12" 37±3mm	1.41±0.12" 37±3mm
5	2.68±0.12" 68±3mm	2.68±0.12" 68±3mm	2.68±0.12" 68±3mm	2.68±0.12" 68±3mm
6	4.75±0.06" 120.65±1.5mm	4.75±0.06" 120.65±1.5mm	4.75±0.04" 120.7±1mm	4.75±0.06" 120.65±1.5mm
A (PORT)	3/8-18NPTF	3/8-18NPTF	M16X1.5	3/8-18NPTF
B (MTG BOLT)	M16X1.5	M16X1.5	M16X1.5	M16X1.5
C (P/ROD)	M16X1.5	M16X1.5	M16X1.5	M16X1.5

